

Panel Data's	
LCD	ASV AGLR
Resolution in dots	1,920 x 1,080
Display colors	16.77 Million (8bit)
Brightness	450cd/m ²
Displaying Mode	Normal Black
Response time in ms	6
Screen Size in mm	1152 x 648
Contrast ratio	1700:01:00
Viewing angle (H / V)	176 / 176

Input Terminals	
Video	DVI-D(24pin) < DVI1.0> (HDCP Support); RGB (mini D-Sub 15pin); RGB (BNC x5)*; Component(Y, Pb/Cb, Pr/Cr :BNC)*; Composite (BNC) -NTSC/PAL/SECAM-
Serial	RS-232C
Audio	Line in (RCA x2) for AV; Line in 2 (3.5mm mini stereo jack) for PC

Output Terminals	
Video	DVI-D (24pin) w/ HDCP
Serial	RS-232C

Audio Data's	
Audio	Line out (RCA x2)
Speaker out	7W 7W [6 Ohm]

Video Systems	
Video color system	NTSC(3.58)/NTSC(4.43)/PAL/PAL60/SECAM

PC Data's	
Compatible signal timing(PC)	Analog (Hsync 31.0 to 81.1 kHz, Vsync 56 to 76.2 kHz); Digital (Hsync 31.0 to 80.0 kHz, Vsync 60 to 75 kHz)

Functions	
User controls	OSD; Remote control×1, IR Type; RS-232C
Plug & play	VESA DDC2B
Gain Control	Auto/ Manual
Enlarge Adjusting	Digital scaling(VGA/SVGA/XGA/SXGA to Full HD)
UXGA scale-down adjusting	•
Manual Adjusting	Clock, Phase, Image Positioning, Black level, Contrast Ratio, Brightness, Color Temperature, Color Mode, Volume, Audio menu (Treble, bass, balance), Remote control×1

OSD Languages	7 Languages (JPN, ENG, GER, FRA, ITA, ESP, RUS)
Auto Adjusting	•
Power-off timer	Yes by Scheduling Function
Scheduling function	•
Adjusting lock	•
Multi-screen capability(enlargement)	Max 5 x 5
Power-on delay	•
Log trace function	•
Bezel image adjustment	•
Image reversing	Yes (Up, down , left, right, all four directions)
Fan	T.B.D
Power management	VESA DPMS, DVI DMPM
PC control and display monitoring	Yes by RS-232C
Daisy chain connection	Yes by DVI (Mirror/ Enlargement) up to 5 displays
Removabel front bezel	•
Portrait Orientation	•
Main power switch	•

Others	
Mounting method	VESA holes (M6 x 6, 200 mm pitch) (P)
Accessories	Power cable, Remote control, Utility disk(CD-ROM), Vertical logo, Temporary stand, Cable clamp, Power cord clamp, Operation manual, Blank sticker, 2 "AA" size batteries

Cabinet	Front: Resin / Back : Aluminum; (Front bezel replacable)
Dimensions (W x D x H) with front bezel in mm	1,133 × 140 × 657
Dimensions (W x D x H) without front bezel in mm	1,255 × 132 × 743
Weight	35,5
Power consumption	266/7
Operating temperature	0 to 40
Operating Humidity	20% to 80% (No-condensing)
Power voltage	100V-240V
EAN-Code	4,97402E+12